

This Page Is Inserted by IFW Operations
and is not a part of the Official Record

BEST AVAILABLE IMAGES

Defective images within this document are accurate representations of the original documents submitted by the applicant.

Defects in the images may include (but are not limited to):

- BLACK BORDERS
- TEXT CUT OFF AT TOP, BOTTOM OR SIDES
- FADED TEXT
- ILLEGIBLE TEXT
- SKEWED/SLANTED IMAGES
- COLORED PHOTOS
- BLACK OR VERY BLACK AND WHITE DARK PHOTOS
- GRAY SCALE DOCUMENTS

IMAGES ARE BEST AVAILABLE COPY.

**As rescanning documents *will not* correct images,
please do not report the images to the
Image Problem Mailbox.**

- 5 -

Commissioner for Patents**AMENDMENTS TO THE ABSTRACT**

A turning device for use in concert with a conveyor adapted to feed elongated wood pieces one by one to the turning device comprises at least one turning member moveable between an idle position and an operational position, a sensor located upstream of the turning member, for scanning the wood pieces on the a conveyor, and an deflector controlled by the sensor and adapted, when actuated, to selectively cause the turning member to be displaced to the operational position for turning a given elongated wood piece on the conveyor to a desired position. The turning member is pivotally mounted to a motorised chain for continuously displacing the turning member adjacent the conveyor. The turning member also includes a guide pin, and the chain drives the turning member along a closed-loop guide track, the turning member having its guide pin engaged in the track. The guide track defines a main section and a secondary section, wherein when in the main section, the turning member remains in its idle position, whereas when the turning member engages the secondary section, it is displaced to its operational position. The deflector is pivotally displaceable between first and second positions by the sensor, whereby in the first position, the turning member displaces in the main section in its idle position, whereas in the second position, the turning member is guided so as to displace in the secondary section in its operational position.